



SPECIFICATION : MODEL EFSFC

| MODEL | | 36 | 60 | 90 | 120 |
|--------------------|--------------------|--------------|-----------|-----------|-----------|
| Cooling Capacity | BTU/hr | 34,000 | 56,000 | 84,000 | 112,000 |
| | kW | 9.9 | 16.4 | 24.6 | 32.8 |
| Heating (optional) | BTU/hr | 36,000 | 60,000 | 90,000 | 120,000 |
| | kW | 10.5 | 17.5 | 26.3 | 35.1 |
| Air Flow | cfm | 1400 | 1800 | 3000 | 3000 |
| | m ³ /hr | 2380 | 3060 | 5100 | 5100 |
| Coil | Area sq. ft. | 4.0 | 4.7 | 9.0 | 9.0 |
| | rows | 2 | 3 | 2 | 3 |
| Blower | qty | 1 | 1 | 2 | 2 |
| | W x φ mm | 180 x 378 | 180 x 378 | 180 x 378 | 180 x 378 |
| Sound Level | dB(A) | 54 | 54 | 57 | 57 |
| Power Supply | V-Ph-Hz | 220/240-1-50 | | | |
| Fan motor | qty | 1 | 1 | 2 | 2 |
| | HP | 1/2 | 1/2 | 1/2 | 1/2 |
| | RLA | 1.9 | 1.9 | 3.8 | 3.8 |
| | Watt | 235 | 235 | 470 | 470 |
| Connection | liquid in | 1/2 | 1/2 | 1/2 | 5/8 |
| | suction in | 3/4 | 3/4 | 1-3/8 | 1-3/8 |
| | drain in | 3/4 | 3/4 | 3/4 | 3/4 |
| Unit Dimensions | Width mm | 590 | 840 | 1090 | 1090 |
| | Depth mm | 380 | 380 | 380 | 380 |
| | Height mm | 1900 | 1900 | 1900 | 1900 |
| NW/ GW | kg | 80 / 90 | 90 / 100 | 170 / 190 | 180 / 200 |

- Digital Electronic Controller
- Wireless IR Remote control
- Air Swing
- Sturdy steel cabinet
- High Air flow for rapid climate control
- Quiet Operation
- Removable and Washable filters
- High efficiency multi speed PSC motor with internal thermal protection
- Cool only or Heat/Cool (optional)

Classic
AIR CONDITIONERS

