



Models / Modelos HWHDBC/HRHDBC



Technical Specifications / Especificaciones Técnicas

Model			HWHDBC12S	HWHDBC18S	HWHDBC24S
Power Supply		V-Ph-Hz	208V~230V,60Hz	208V~230V,60Hz	208V~230V,60Hz
Cooling	Capacity (range)	Btu/h	12000	18000	24000
	Rated current	A	4.1	6.3	9.2
	SEER	Btu/w	20.5	23.3	20.5
Heating	Capacity	Btu/h	13000	19000	24500
	Rated current	A	5.0	7.2	9.3
	HSPF4	Btu/w	10.8	11.6	11.8
Compressor	Type		Rotary	Rotary	Rotary
	Brand		GMCC	GMCC	GMCC
Indoor air flow		m3/h	620	1100	1200
Indoor noise level (Hi/Mi/Lo/silence)		dB(A)	39 / 32 / 29 / 26	45 / 41 / 37 / 34	48 / 45 / 40 / 36
Indoor unit	Dimension(W*D*H)	mm	835x280x220	1100x325x244	1100x325x244
	Dimension(W*D*H)	inch	32 7/8x11x8 11/16	43 5/16x12 13/16x9 5/8	43 5/16x12 13/16x9 5/8
	Packing (W*D*H)	mm	870x335x265	1170x390x315	1170x390x315
	Packing (W*D*H)	inch	34 1/4x13 3/16x10 7/16	46 1/16x15 3/8x12 7/16	46 1/16x15 3/8x12 7/16
	Net/Gross weight	Kg	9.0/11.0	14.5 / 17.0	14.5 / 17.0
	Net/Gross weight	lbs.	19.8 / 24.2	31.9 / 37.4	31.9 / 37.4
Outdoor unit	Dimension(W*D*H)	mm	810x585x280	860x650x310	885x795x366
	Dimension(W*D*H)	inch	31 7/8x23x11	33 7/8x25 9/16x12 3/16	34 7/8x31 5/16x14 3/8
	Packing (W*D*H)	mm	940x640x385	995x730x445	1050x890x500
	Packing (W*D*H)	inch	37x25 3/16x15 3/16	39 3/16x28 3/4x17 1/2	41 11/32x35x19 11/16
	Net/Gross weight	Kg	33.0 / 36	45 / 49	56 / 64
	Net/Gross weight	lbs.	72.7 / 79.3	99.2 / 108	123.4 / 141
Refrigerant			R410A	R410A	R410A
Refrigerant charge volume		g	1160	1550	1880
Room Temperature	Cooling	(°C/°F)	-15°C-46°C; (5°F-115°F)	-15°C-46°C; (5°F-115°F)	-15°C-46°C; (5°F-115°F)
	Heating	(°C/°F)	-20°C-24°C; (-4°F-75°F)	-20°C-24°C; (-4°F-75°F)	-20°C-24°C; (-4°F-75°F)

Features and Benefits

